


BCD CABLES TYPE B04



BS6883 Shipwiring Cable 600/1000v

Power & Control Cable for fixed installation in ships & offshore structures in areas that require mechanical protection

Construction:

Class 2 Flexible Plain Copper Conductors/EPR insulation/SW4 Bedding/
Phosphor Bronze Wire Braid/SW4 Halogen Free Low Smoke Sheath

Single Core 6591D

SIZE SQ.MM	MAX DIAM OVER CONDUCTOR MM	RT OF INSULATION MM	DIAMETER OVER CORE MM	RT OF BEDDING MM	DIAMETER OVER BEDDING MM	DIAMETER OF BRAID WIRE MM	DIAMETER OVER BRAID MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.0	1.20	0.8	2.8	1.0	5.2	0.3	6.7	8.8	145
1.5	1.50	0.8	3.1	1.0	5.5	0.3	7.0	9.3	155
2.5	2.01	0.8	3.6	1.0	6.0	0.3	7.5	9.8	175
4	2.55	1.0	4.6	1.0	6.9	0.3	8.4	10.8	205
6	3.12	1.0	5.2	1.0	7.5	0.3	9.0	11.4	235
10	4.05	1.0	6.5	1.0	9.0	0.3	10.5	13.1	330
16	5.10	1.0	7.5	1.0	10.1	0.3	11.6	14.2	405
25	6.75	1.2	9.6	1.2	12.4	0.3	13.9	16.7	565
35	7.65	1.2	10.5	1.2	13.3	0.3	14.8	17.8	635
50	8.90	1.4	12.1	1.4	15.2	0.3	16.7	19.7	820
70	10.70	1.4	13.9	1.4	17.2	0.3	18.7	22.1	1060
95	12.46	1.6	16.1	1.6	19.3	0.3	20.8	24.4	1370
120	14.21	1.6	17.8	1.6	21.4	0.3	22.9	26.6	1650
150	15.75	1.8	19.8	1.8	23.5	0.3	25.0	28.9	2010
185	17.64	2.0	22.0	2.0	26.0	0.45	28.3	32.5	2570
240	20.25	2.2	25.0	2.2	29.2	0.45	31.5	36.0	3250
300	22.68	2.4	27.9	2.4	32.3	0.45	34.6	39.4	4000
400	26.66	2.6	32.2	2.6	36.4	0.45	38.7	43.9	5340
500	29.15	2.8	35.2	2.8	40.2	0.45	42.5	48.1	6540
630	32.76	2.8	38.8	2.8	44.1	0.45	46.4	52.3	8000



www.bcd-cables.com

T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com