


BCD CABLES



BS6195 Type 4C Coil End Lead/Battery Cable
Flexible Class 5 Tinned Copper Conductors, Composite EPR/HOFR CSP Insulation
600/1000v -20 to +85°C

Size mm ²	Stranding	Nom RT of Ins	Overall Diameter
		Volt. Cat.	
		C	C
	mm		
0.5	16/0.2	1.4	4.5
0.75	24/0.2	1.4	4.7
1	32/0.2	1.4	4.9
1.5	30/0.25	1.4	5.2
2.5	50/0.25	1.4	5.6
4	56/0.3	1.4	6.3
6	84/0.3	1.5	7.5
10	80/0.4	1.5	8.5
16	126/0.4	1.5	9.6
25	196/0.4	1.6	11.4
35	276/0.4	1.6	12.8
50	396/0.4	1.7	14.8
70	360/0.5	1.8	17.2
95	475/0.5	2	19.2
120	608/0.5	2.2	21.9
150	756/0.5	2.3	24.1
185	925/0.5	2.4	26.3
240	1221/0.5	2.4	28.3
300	1525/0.5	2.6	33
400	2013/0.5	2.8	37.4
630	2106/0.6	-	-



www.bcd-cables.com

T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com