


BCD CABLES TYPE C19



Lightweight Halogen Free Ships Cable 60/250v
Instrument/Telecomms Cable for fixed installation in ships & offshore structures in areas that require electrical tape screen

Construction:

Class 2 Plain Copper Conductors/XL100 insulation/Collective Ali/Polyester Tape/Flambar Tape
SHF1 Halogen Free Sheath

Nominal dimensional and electrical data						60V - 250V
CONSTRUCTION (mm)	INSULATION THICKNESS (mm)	OUTER SHEATH THICKNESS (mm)	OVERALL DIAMETER APPROX (mm)	WEIGHT APPROX (1kg/km)	BENDING RADIUS (mm)	CONDUCTOR RESISTANCE AT 20 Deg C (A)
1 x 2 x 0.5	0.7	1.0	7	60	30	41.6
2 x 2 x 0.5	0.7	1.1	10.5	100	40	41.6
4 x 2 x 0.5	0.7	1.2	12.5	155	50	41.6
7 x 2 x 0.5	0.7	1.3	15.0	230	60	41.6
10 x 2 x 0.5	0.7	1.4	18.0	305	70	41.6
14 x 2 x 0.5	0.7	1.5	20.5	405	80	41.6
19 x 2 x 0.5	0.9	1.6	23.5	525	95	41.6
24 x 2 x 0.5	0.7	1.7	26.0	650	105	41.6
30 x 2 x 0.5	0.7	1.8	29.0	790	115	41.6
1 x 3 x 0.5	0.7	1.0	7.5	70	30	41.6
1 x 4 x 0.5	0.7	1.0	8.0	80	30	41.6
1 x 2 x 0.75	0.7	1.0	7.5	65	30	26.6
2 x 2 x 0.75	0.7	1.2	11.5	115	45	26.6
4 x 2 x 0.75	0.7	1.2	13.0	180	50	26.6
7 x 2 x 0.75	0.7	1.3	16.0	270	65	26.6
10 x 2 x 0.75	0.7	1.5	19.0	385	80	26.6
14 x 2 x 0.75	0.7	1.6	20.5	505	90	26.6
19 x 2 x 0.75	0.7	1.7	23.5	655	100	26.6
24 x 2 x 0.75	0.7	1.8	26.0	815	115	26.6
30 x 2 x 0.75	0.7	1.9	29.0	990	125	26.6
1 x 3 x 0.75	0.7	1.0	8.0	80	30	26.6
4 x 3 x 0.75	0.7	1.3	14.5	240	60	26.6
7 x 3 x 0.75	0.7	1.4	18.5	370	75	26.6
10 x 3 x 0.75	0.7	1.6	22.5	430	90	26.6
14 x 3 x 0.75	0.7	1.7	25.0	695	100	26.6
19 x 3 x 0.75	0.7	1.8	29.0	915	115	26.6
1 x 4 x 0.75	0.7	1.1	9.0	95	40	26.6
1 x 2 x 1.5	0.7	1.1	8.5	90	35	12.2
2 x 2 x 1.5	0.7	1.2	13.0	170	50	12.2
4 x 2 x 1.5	0.7	1.3	15.5	265	60	12.2
7 x 2 x 1.5	0.7	1.4	18.5	410	75	12.2
10 x 2 x 1.5	0.7	1.6	22.0	585	90	12.2
14 x 2 x 1.5	0.7	1.7	24.5	775	105	12.2
19 x 2 x 1.5	0.7	1.9	28.0	1040	120	12.2
24 x 2 x 1.5	0.7	2.0	31.0	1280	135	12.2
30 x 2 x 1.5	0.7	2.1	34.5	1470	150	12.2
1 x 3 x 1.5	0.7	1.1	9.0	115	35	12.2
4 x 3 x 1.5	0.7	1.4	17.0	360	70	12.2
7 x 3 x 1.5	0.7	1.6	22.0	590	85	12.2
10 x 3 x 1.5	0.7	1.7	26.5	825	105	12.2
14 x 3 x 1.5	0.7	1.8	29.5	1095	120	12.2
19 x 3 x 1.5	0.7	2.0	34.0	1455	135	12.2
1 x 4 x 1.5	0.7	1.1	10.0	135	40	12.2



www.bcd-cables.com

T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com