


# BCD CABLES TYPE D32



## Halogen Offshore Cable 60/250v BFOU(i)

Fire Resistant Instrumentation Cable for fixed installation in ships & offshore structures in areas that require mechanical protection & enhanced electrical screening.

### Construction:

Class 2 Tinned Copper Conductors/EPR insulation/Individual Copper Tape Screen/SHF2 Bedding/Tinned Copper Wire Braid/SHF21 Halogen Free & Mud Resistant Sheath

### NEK 606 Type BFOU (i)

60/250v

pairs/ triples	Conductor			Insulation thickness	Inner covering thickness	Diameter over inner covering	Overall diameter	Approx. cable weight
	Size	Const.	Dia.					
-	mm <sup>2</sup>	No./mm	mm	mm	mm	mm	mm	kg/km
2P	0.75	7/0.37	1.11	0.8	1	15	20.4	727
4P	0.75	7/0.37	1.11	0.8	1	17.6	23.3	951
7P	0.75	7/0.37	1.11	0.8	1	22.5	28.5	1402
8P	0.75	7/0.37	1.11	0.8	1	23.4	29.5	1481
10P	0.75	7/0.37	1.11	0.8	1	26.4	32.8	1834
12P	0.75	7/0.37	1.11	0.8	1.2	27.7	34.2	2019
24P	0.75	7/0.37	1.11	0.8	1.4	39.3	47.3	3985
1T	0.75	7/0.37	1.11	0.8	1	9.6	14	335
2T	0.75	7/0.37	1.11	0.8	1	16.8	22.4	857
4T	0.75	7/0.37	1.11	0.8	1	19.8	25.6	1133
8T	0.75	7/0.37	1.11	0.8	1	26.3	32.6	1819
12T	0.75	7/0.37	1.11	0.8	1.2	32.8	39.7	2628
2P	1.5	7/0.53	1.59	0.8	1	16.7	22.3	866
4P	1.5	7/0.53	1.59	0.8	1	19.7	25.5	1156
7P	1.5	7/0.53	1.59	0.8	1	25.2	31.5	1733
8P	1.5	7/0.53	1.59	0.8	1	26.3	32.6	1830
12P	1.5	7/0.53	1.59	0.8	1.2	31.1	38.4	2738
24P	1.5	7/0.53	1.59	0.8	1.4	44.2	52.6	5011
2T	1.5	7/0.53	1.59	0.8	1	18.7	24.4	1025
4T	1.5	7/0.53	1.59	0.8	1	22	28	1389
8T	1.5	7/0.53	1.59	0.8	1.2	29.8	36.5	2325
12T	1.5	7/0.53	1.59	0.8	1.2	36.7	44.5	3574



[www.bcd-cables.com](http://www.bcd-cables.com)

T: +44 1493 604604 F: +44 1493 60466 E: [sales.bcd@etechcentre.com](mailto:sales.bcd@etechcentre.com)