


BCD CABLES TYPE F17

H07RN-F Rubber Flexible Cable 450/750v



Construction:

Flexible Class 5 Plain Copper Conductors, EPR Insulation, PCP Sheath,

Size mm ²	Cores	Nominal Thickness of Insulation mm	Nominal Diameter of Over Laid Up Cores mm	Nominal Overall Diameter mm	Nominal Weight kg/Km	Gland (Brass)	Gland (Nylon)
4	1	1	4.7	7.8	115	-	20
6	1	1	5.7	9	142	20	20
10	1	1.2	7.1	10.8	219	20S	20
16	1	1.2	8.2	12.1	302	20	20L
25	1	1.4	10	14.1	436	25	25
35	1	1.4	11.4	15.9	567	25	25
50	1	1.6	13.6	18.5	790	25	32
70	1	1.6	15.7	21	1050	32	32
95	1	1.8	18.2	23.9	1350	32	32
120	1	1.8	19.7	25.8	1650	32	40
150	1	2	22.1	28.6	2050	40	40
185	1	2.2	24.5	31.5	2450	40	40
240	1	2.4	27.9	35.1	3200	50S	50
300	1	2.6	31.2	38.7	3900	50	-
400	1	2.8	35.7	43.5	5000	50	-
500	1	3	39.6	47.5	6200	63S	-
630	1	3	43.1	51.5	7650	63	-
1	2	0.8	5.9	8.6	95	20S	20
1.5	2	0.8	6.5	9.6	115	20S	20
2.5	2	0.9	7.7	11.2	140	20S	20
4	2	1	9.5	13.2	302	20	20L
6	2	1	11.5	15.6	400	25	25
10	2	1.2	14.3	20.6	750	32	32
16	2	1.2	16.5	23.3	990	32	32
25	2	1.4	20.1	27.4	1400	40	40
1	3	0.8	6.4	9.3	115	20S	20
1.5	3	0.8	7	10.3	140	20S	20
2.5	3	0.9	8.3	12	200	20	20
4	3	1	10.2	14.1	360	25	25
6	3	1	12.3	16.6	490	25	25
10	3	1.2	15.4	22.1	900	32	32
16	3	1.2	17.7	24.8	1200	32	32
25	3	1.4	21.6	29.3	1700	40	40
35	3	1.4	24.6	32.9	2200	50S	50
50	3	1.6	29.4	38.5	3100	50	-
70	3	1.6	33.9	43.6	4130	63S	-
95	3	1.8	39.3	50	5300	63	-
120	3	1.8	42.5	53.9	6700	63	-
150	3	2	47.7	59.9	8000	75S	-
185	3	2.2	52.9	65.9	9700	75	-
240	3	2.4	60.3	74.7	12400	90	-
300	3	2.6	67.6	83.2	15300	-	-
1	4	0.8	7.2	10.3	140	20S	20
1.5	4	0.8	7.8	11.4	170	20S	20
2.5	4	0.9	9.3	13.2	245	20	20L
4	4	1	11.4	15.5	460	25	25
6	4	1	13.8	18.5	610	25	32
10	4	1.2	17.2	24.1	1100	32	32
16	4	1.2	19.8	27.1	1500	40	40
25	4	1.4	24.2	32.5	2310	50S	50
35	4	1.4	27.6	36.5	2800	50S	50
50	4	1.6	32.9	42.6	3910	50	-
70	4	1.6	38	48.6	5200	63	-
95	4	1.8	44	56	6810	75S	-
120	4	1.8	47.7	59.9	8200	75S	-
150	4	2	53.6	66.8	10200	75	-
185	4	2.2	59.3	73.5	12300	90	-
240	4	2.1	67.6	83.5	15900	-	-
300	4	2.6	75.8	92.8	19600	-	-
1.5	5	0.8	8.8	12.5	210	20	20L
2.5	5	0.9	10.4	14.5	305	25	25
4	5	1	12.7	17.2	560	25	25
6	5	1	15.4	20.5	750	32	32
10	5	1.2	19.2	26.5	1300	40	40
16	5	1.2	22.2	30.1	1800	40	40
25	5	1.4	27.1	36.1	2600	50S	50
35	5	1.4	30.9	40.5	3590	50	-



www.bcd-cables.com



T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com