


BCD CABLES TYPE D30



Halogen Offshore Cable 60/250v RFOU(c)

Flame Retardant Instrumentation Cable for fixed installation in ships & offshore structures in areas that require mechanical protection & electrical screening.

Construction:

Class 2 Tinned Copper Conductors/EPR insulation/Collective Copper Tape Screen/SHF2 Bedding/Tinned Copper Wire Braid/SHF21 Halogen Free & Mud Resistant Sheath

NEK 606 Type RFOU (c)

60/250v

pairs/ triples	Conductor			Insulation thickness	Inner covering thickness	Diameter over inner covering	Overall diameter	Approx. cable weight
	Size	Const.	Dia.					
-	mm2	No./mm	mm	mm	mm	mm	mm	kg/km
2P	0.75	7/0.37	1.11	0.8	1	12.1	17.3	542
4P	0.75	7/0.37	1.11	0.8	1	14.1	19.4	679
7P	0.75	7/0.37	1.11	0.8	1	16.3	21.8	856
8P	0.75	7/0.37	1.11	0.8	1	18	23.6	970
12P	0.75	7/0.37	1.11	0.8	1	21.3	27.3	1281
16P	0.75	7/0.37	1.11	0.8	1	24.1	30.3	1559
24P	0.75	7/0.37	1.11	0.8	1.2	29.2	35.9	2134
2T	0.75	7/0.37	1.11	0.8	1	14	19.3	661
4T	0.75	7/0.37	1.11	0.8	1	16.3	21.9	847
8T	0.75	7/0.37	1.11	0.8	1	21.6	27.5	1300
12T	0.75	7/0.37	1.11	0.8	1	26.4	32.8	1791
2P	1.5	7/0.53	1.59	0.8	1	13.8	19.1	664
4P	1.5	7/0.53	1.59	0.8	1	16.1	21.6	855
7P	1.5	7/0.53	1.59	0.8	1	18.7	24.4	1107
8P	1.5	7/0.53	1.59	0.8	1	20.7	26.5	1254
12P	1.5	7/0.53	1.59	0.8	1	24.6	30.8	1696
2T	1.5	7/0.53	1.59	0.8	1	15.9	21.4	819
4T	1.5	7/0.53	1.59	0.8	1	18.7	24.4	1081
8T	1.5	7/0.53	1.59	0.8	1	24.8	31	1713
12T	1.5	7/0.53	1.59	0.8	1.2	30.9	38.2	2653



www.bcd-cables.com

T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com