


BCD CABLES TYPE D32



Halogen Offshore Cable 60/250v RFOU(i)

Flame Retardant Instrumentation Cable for fixed installation in ships & offshore structures in areas that require mechanical protection & enhanced electrical screening.

Construction:

Class 2 Tinned Copper Conductors/EPR insulation/Individual Copper Tape Screen/SHF2 Bedding/Tinned Copper Wire Braid/SHF21 Halogen Free & Mud Resistant Sheath

NEK 606 Type RFOU (i)

60/250v

pairs/ triples	Conductor			Insulation thickness	Inner covering thickness	Diameter over inner covering	Overall diameter	Approx. cable weight
	Size	Const.	Dia.					
-	mm ²	No./mm	mm	mm	mm	mm	mm	kg/km
2P	0.75	7/0.37	1.11	0.8	1	12.9	18.1	596
4P	0.75	7/0.37	1.11	0.8	1	15.1	20.5	776
7P	0.75	7/0.37	1.11	0.8	1	19.1	24.9	1128
8P	0.75	7/0.37	1.11	0.8	1	19.9	25.7	1187
12P	0.75	7/0.37	1.11	0.8	1	23.1	29.2	1583
16P	0.75	7/0.37	1.11	0.8	1	25.9	32.2	1944
24P	0.75	7/0.37	1.11	0.8	1.2	32.8	40.3	3125
2T	0.75	7/0.37	1.11	0.8	1	14.3	19.6	695
4T	0.75	7/0.37	1.11	0.8	1	16.7	22.3	920
8T	0.75	7/0.37	1.11	0.8	1	22.2	28.2	1472
12T	0.75	7/0.37	1.11	0.8	1.2	27.6	34.1	2126
2P	1.5	7/0.53	1.59	0.8	1	14.6	20	724
4P	1.5	7/0.53	1.59	0.8	1	17.2	22.8	962
7P	1.5	7/0.53	1.59	0.8	1	21.8	27.8	1427
8P	1.5	7/0.53	1.59	0.8	1	22.7	28.8	1501
12P	1.5	7/0.53	1.59	0.8	1	26.5	32.9	2035
16P	1.5	7/0.53	1.59	0.8	1.2	30.2	37.4	2768
24P	1.5	7/0.53	1.59	0.8	1.4	38.1	46	4093
2T	1.5	7/0.53	1.59	0.8	1	16.2	21.7	851
4T	1.5	7/0.53	1.59	0.8	1	19.1	24.9	1149
8T	1.5	7/0.53	1.59	0.8	1	25.4	31.7	1871
12T	1.5	7/0.53	1.59	0.8	1.2	31.7	39	2925



www.bcd-cables.com

T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com