


BCD CABLES TYPE F08

SY Flexible Control Cable 300/500v



Construction:

Flexible Class 5 Plain Copper Conductors, PVC Insulation, PVC Bedding
Galvanised Steel Wire Braid, PVC Sheath, Transparent

No. of Cores	Nominal Cross Sectional Area mm ²	Nominal No. and Size of Wires # / mm	Nominal Overall Diameter mm	Nominal Weight kg/Km	Gland Size
3	1	32/0.20	9	142	20S
3	1.5	30/0.25	10.2	186	20S
3	2.5	50/0.25	11.9	246	20
3	4	56/0.30	15.1	330	25
3	6	84/0.30	16.2	407	25
3	10	80/0.40	20.1	621	32
3	16	126/0.40	23.8	857	32
4	1	32/0.20	9.8	165	20S
4	1.5	30/0.25	10.9	212	20S
4	2.5	50/0.25	13.4	315	25
4	4	56/0.30	16.4	457	25
4	6	84/0.30	19.5	687	32
4	10	80/0.40	24.2	1009	32
4	16	126/0.40	27.1	1384	40
5	1	32/0.20	10.5	197	20S
5	1.5	30/0.25	11.7	241	20
5	2.5	50/0.25	14.5	365	25
5	4	56/0.30	17.7	545	25
5	6	84/0.30	21.1	798	32
5	10	80/0.40	26.2	1197	40
5	16	126/0.40	30.6	1740	40
7	1	32/0.20	11.2	231	20
7	1.5	30/0.25	13.1	310	20
7	2.5	50/0.25	15.5	458	25



www.bcd-cables.com



T: +44 1493 604604 F: +44 1493 60466 E: sales.bcd@etechcentre.com