


# BCD CABLES

YY Flexible Control Cable 300/500v



**Construction:**

Flexible Class 5 Plain Copper Conductors, PVC Insulation, PVC Sheath, Grey

Number of Cores	Nominal Cross Sectional Area mm <sup>2</sup>	No. and Nominal Diameter of Strands #/mm	Nominal Overall Diameter mm	Nominal Weight kg/ km
3	0.75	24/0.20	5.9	55
3	1	32/0.20	6.4	67
3	1.5	30/0.25	7.4	92
3	2.5	50/0.25	9.5	153
3	4	56/0.30	12	235
3	6	84/0.30	12.8	305
3	10	80/0.40	15.8	590
3	16	126/0.40	18.4	800
4	0.75	24/0.20	6.8	76
4	1	32/0.20	7.4	89
4	1.5	30/0.25	8.5	122
4	2.5	50/0.25	10.4	191
4	4	56/0.30	13.5	330
4	6	84/0.30	16	480
4	10	80/0.40	20.8	743
4	16	126/0.40	24.1	1104
5	0.75	24/0.20	7.4	88
5	1	32/0.20	8.1	108
5	1.5	30/0.25	9.3	148
5	2.5	50/0.25	11.7	241
5	4	56/0.30	14.7	404
5	6	84/0.30	17.2	592
5	10	80/0.40	22.9	920
5	16	126/0.40	28.4	1370
7	0.75	24/0.20	8	113
7	1	32/0.20	8.8	140
7	1.5	30/0.25	10.1	193
7	2.5	50/0.25	12.9	311



[www.bcd-cables.com](http://www.bcd-cables.com)



T: +44 1493 604604 F: +44 1493 60466 E: [sales.bcd@etechcentre.com](mailto:sales.bcd@etechcentre.com)